

Hisense
life reimagined



Model No.		AS-09HR4SYDTE	AS-12HR4SVDTE	AS-18HR4SWATE	AS-24HR4SFBTE
Type		H/P, ON/OFF	H/P, ON/OFF	H/P, ON/OFF	H/P, ON/OFF
Cooling Capacity	W	2700	3600	5000	6800
Heating Capacity	W	2750	3700	5200	7100
Rated Input-Cooling	W	840	1121	1555	2115
Rated Input-Heating	W	755	1025	1440	1965
Air Circulation (indoor)	m ³ /h	500	500	1050	1200
EER for Cooling	W/W	3,21	3,21	3,21	3,21
COP for Heating	W/W	3,64	3,61	3,61	3,61
Refrigerant		R410A	R410A	R410A	R410A
Indoor Unit Noise Level	High (dB)	40	40	46	50
	Low (dB)	35	35	39	45
Outdoor Unit Noise Level	dB (A)	53	55	58	58
Voltage, Frequency, Phase	V	220-240V, 50Hz, 1P	220-240V, 50Hz, 1P	220-240V, 50Hz, 1P	220-240V, 50Hz, 1P
Rated Current	Cooling (A)	3,8	5	7	9,5
	Heating (A)	3,4	4,6	6,5	8,8
Maximum Pipe Length	m	10	10	15	20
Maximual Heights' Interval	m	5	5	7,5	10
LRA	A	21,7	25	25,9	43
Liquid Pipe	inch	1/4	1/4	1/4	3/8
Gas Pipe	inch	3/8	1/2	1/2	5/8
Dimensions WxHxD (mm)	Indoor Unit	780x270x208	780x270x208	960x315x230	1131x315x230
	Outdoor Unit	660x482x240	715x240x482	760x545x255	830x634x287
Weight (Kg)	Indoor Unit	8	8,4	12	14,5
	Outdoor Unit	24	27	36	45